

MADE IN ITALY



EST. 1949 | MILAN

WOOD COATINGS EXTERIOR

WINDOWS & FRAMES

Protect the wood from the harmful effects of the sun, rain, humidity and temperature variations.

In addition to protection, paints for window frames are an opportunity to enhance the wood through the choice of finishes and colors. The options are endless from clear varnishes that leave the natural look of the wood intact to opaque varnishes that offer full coverage or semi-transparent varnishes that impart a slight tint to the wood without completely covering its structure.



SIVAM Coatings S.r.l.
Via Monviso 10 | 20008 Bareggio (MI) - Italy | +39 02 903041 | info@sivam.it

sivam.it   



REDUCTION OF VOC EMISSIONS

Important reduction of VOC emissions (90-95%).

OVERSPRAY

Overspray reduction up to 25%.

GREAT PERFORMANCES

Comparable to those of solventborne systems for most of the applications.

POT-LIFE

Unlimited pot-life with 1K products.

READY TO USE

Ready-to-use products (1K).

NON-FLAMMABLE

Non-flammable products, meaning a safer storehouse.

ODORLESS

They're usually odorless (ideal for on-site application).

WOOD COATINGS EXTERIOR

PRODUCT	CODE	DESCRIPTION	CHARACTERISTICS	APPLICATION	COMPLETE DRY TIME	VERTICAL HOLD	SOLIDS %
PRIMERS							
AQUASIV 2	LWW200	Primer for Softwood	Protection and decoration of softwood against light, weather, fungi and rot	Dip, brush, flow coating	6 h	None	10 ± 2
AQUASIV 8	LWW800	Primer for Hardwood	Protection and decoration of hardwood against light, weather, fungi and rot	Dip, brush, flow coating	3 - 4 h	None	10 ± 2
AQUASIV 274	LWW274	White Primer	Protection and decoration of softwood against light, weather, fungi and rot	Dip, brush, flow coating	4 h	None	30 ± 2
2K INSULATORS							
IDRODUR 150	LVA150	Clear 2K Insulating Sealer	Great tannin retention	Spray	16 - 24 h	Good	30 ± 2
IDROFOND 130	LVR130	White 2K Insulating Sealer	Great tannin retention	Spray	16 - 24 h	Good	38 ± 2
TRANSPARENT BASECOATS							
AQUAVER 100	LWY100	Clear Basecoat	Very good transparency and filling power, easily sandable	Airless and air-mix pumps	12 h	Great	38 ± 2
WHITE BASECOATS							
AQUAPRIMER 522	LWY522	White Basecoat	Fast drying, great filling power and sandability	Airless and air-mix pumps	6 - 8 h	Great	50 ± 2
AQUAPRIMER 512	LWY512	Tannin-insulating White Basecoat	Good coverage and insulation by tannins and other substances from wood, one component	Airless and air-mix pumps	10 - 12 h	Great	48 ± 2
AQUAPRIMER 525	LWY525	Tannin-insulating White 2K Basecoat	Great insulation of wood tannins	Airless and air-mix pumps	16 - 24 h	Great	50 ± 2
TRANSPARENT TOPCOATS							
AQUATOP 01	LWY01 SERIE	Transparent Topcoat	Great aesthetic result and protection against UV rays	Airless and air-mix pumps	24 h	Excellent	40 ± 2
AQUATOP 31	LWY31 SERIE	Transparent Topcoat	Like AQUATOP 01, suitable for airbrush application	Airbrush	24 h	Great	39 ± 2
AQUATOP 25	LWY25 SERIE	Transparent Topcoat	Like AQUATOP 01, suitable for brush application	Brush	24 h	Good	40 ± 2
PIGMENTED TOPCOATS							
AQUAFLAT 60	LWY60 SERIE	White Topcoat/Converter	Can be tinted into opaque pastel colours	Airless and air-mix pumps	24 h	Excellent	44 ± 2
AQUAFLAT 62	LWY62 SERIE	White Topcoat	Like AQUAFLAT 60, suitable for airbrush application	Airbrush	24 h	Great	44 ± 2
AQUAFLAT 65	LWY65 SERIE	White Topcoat	Like AQUAFLAT 60, suitable for brush application	Brush	24 h	Good	48 ± 2
AQUAFLAT CONV 15	LXY15 SERIE	Neutral Converter	Can be tinted into opaque colours	Airless and air-mix pumps	24 h	Excellent	39 ± 2

KINGFISHER COLOR CLASSIC

The collection offers a range of shades inspired by the finest wood essences, allowing you to obtain elegant and natural finishes that respect and enhance the grain and structure of the wood. Each colour is designed to give the wood an authentic and refined appearance, while ensuring protection and durability over time.

